

Frame Dimensions & Structural Openings

Door Width	Lining Depth	Fitting Tolerance	Overall Door Kit Width	Structural Opening Width
533mm (21")	25mm	2mm	587mm	592mm
610mm (24")	25mm	2mm	664mm	669mm
686mm (27")	25mm	2mm	740mm	745mm
762mm (30")	25mm	2mm	816mm	821mm
813mm (32")	25mm	2mm	867mm	872mm
838mm (33")	25mm	2mm	892mm	897mm
526mm	25mm	2mm	580mm	585mm
626mm	25mm	2mm	680mm	685mm
726mm	25mm	2mm	780mm	785mm
826mm	25mm	2mm	880mm	885mm
926mm	25mm	2mm	990mm	995mm

The fitting tolerance relates to the gap between the door and the lining, this is 2mm on each side.

The above dimensions are the same for all Fire Doors and non-Fire Doors.

The gap allowed under the door for floor coverings is 20mm and the frame will need to be cut down in accordance to individual floor coverings.

Adjustable Hinges

All hinges on Simpli Doorsets are 3D adjustable clip-on hinges. The hinges can be adjusted by +/- 2.5mm in all directions (i.e. vertically, horizontally and laterally).



Handles

The handles available on the Doorsets are from the XL Joinery handle range.